



WHEN THERE'S A JOB TO BE DONE. With 28,000 lb (124.6 kN) of thrust/pullback and 4200 ft-lb (5694.4 Nm) of rotational torque, the D24x40 S3 offers an increase over its predecessor, helping to maximize machine and jobsite productivity.



TOP OF ITS CLASS. With a class-leading carriage speed of 240 fpm (73.2 m/min) - more than 20% faster than its closest competitor - the D24x40 S3 helps contractors install more linear feet per day.



INSTALL PRODUCT FASTER. The D24x40 S3 features a 270 rpm rotational speed that rivals larger drills and outpaces competitive models by 18% - helping contractors complete jobs faster.



SIGNIFICANT SOUND REDUCTION. With a 104 dB(A) guaranteed sound power level and an operator ear rating of 82.9 dB(A), as well as an in-cab operator ear rating of 75.7 dB(A), the D24x40 S3 contributes to a quieter working environment, creating less neighborhood disturbance and enabling easier communication among the crew.



COMFORTABLE CAB. The excavator-style cab offers operators more legroom and greater comfort.



AURORA™ TOUCHSCREEN DISPLAY. Interactive full-color touchscreen display delivers real-time, easy-to-view locate information, bore plans and more that can help increase productivity.









🛂 👛 💟 💀 VERMEER.COM



D24x40 S3 NAVIGATOR® HORIZONTAL DIRECTIONAL DRILL

GENERAL WEIGHTS AND DIMENSIONS

Min transport length: 20.1' (6.1 m)
Min transport width: 89" (226.1 cm)
Min transport height: 76" (193 cm)
Height (with cab): 102" (259.1 cm)
Min weight: 20,700 lb (9389.3 kg)
Max weight: 22,250 lb (10,092.4 kg)

ENGINE OPTION ONE

Make and model: John Deere 4045 Fuel type: Ultra low sulfur diesel Max engine rpm: 2400 rpm

Gross horsepower: 125 hp (93 kW) Displacement: 275 cu in (4.5 L)

Cooling method: Liquid
Aspiration: Turbo

Emissions rating: Tier 4 Final (EU Stage IV)

ENGINE OPTION TWO

Make and model: John Deere 4045

Fuel type: Diesel

Max engine rpm: 2400 rpm

Gross horsepower: 125 hp (93 kW) Displacement: 275 cu in (4.5 L)

Cooling method: Liquid

Aspiration: Turbo

Emissions rating: Tier 3 (EU Stage IIIA)

OPERATIONAL

Thrust/Pullback: 28,000 lb (124.6 kN)

Max carriage speed at max engine rpm: 240 fpm (73.2 m/min)

Max spindle torque (low at max engine rpm): 4200 ft-lb (5694.4 Nm)

Max spindle speed at max engine rpm: 270 rpm

Min bore diameter: 4" (10.2 cm)

Max ground drive speed at max engine rpm (fwd): 3.3 mph (5.3 km/h)

Noise level at operator's ear: 82.9 dB(A) Noise level at operator's ear (cab): 75.7 dB(A)

Drill rack angle: 14-21° (24.9–38.4%)

FLUID CAPACITIES

Fuel tank: 44 gal (166.6 L)

Antifreeze tank capacity: 3.9 gal (14.7 L)

DRILLING FLUID SYSTEM

Max flow: 50 gpm (189.3 L/min)
Max pressure: 1050 psi (7.2 MPa)

FEATURES

Breakout system: Standard hydraulic vise

Drilling lights: Standard
Flow indicator: Standard
Stakedown system: Standard

Cab: Optional

Strike alert: Standard

Remote lockout: Standard

DRILL PIPE

NOTES:

Type: Firestick® drill rod

Length: 10' (3 m)

Rod diameter: 2.38" (6 cm) Weight: 73 lb (33.1 kg) Bend radius: 108.2' (33 m)

Vermeer

